

Inch Series	Size	Side	Approved rim width	Overall Diameter
20 45	305/45R20 112H	RBL	9.5~11.5	782
	55 LT305/55R20 121/118S	RBL	① 8.5~11	① 844
	60 LT325/60R20 121/118S	RBL	① 9~12	① 898
18 55	225/55R18 98H	RBL	① 6~8	① 705
	60 265/60R18 110H	RBL	7.5~9.5	775
	275/60R18 112H	RBL	① 7.5~9.5	① 787
	285/60R18 116H	RBL	8~10	799
	65 LT275/65R18 113/110S	OWL/RBL	① 7.5~9	① 815
	LT275/65R18 123/120R	RBL	① 7.5~9	① 815
	LT285/65R18 121/118R	RBL	① 8~10	① 827
	70 P265/70R18 114S	RBL	① 7~9	① 829
17 60	215/60R17 96H	RBL	6~7.5	690
	225/60R17 99H	RBL	6~8	702
	P275/60R17 110S	OWL/RBL	① 7.5~9.5	① 762
65	225/65R17 102H	RBL	6~8	724
	235/65R17 108H	RF RBL	6.5~8.5	738
	245/65R17 107H	RBL	7~8.5	750
	255/65R17 110H	RBL	7~9	764
	265/65R17 112H	RBL	7.5~9.5	776
	275/65R17 115H	RBL	7.5~9.5	790
	285/65R17 116H	RBL	8~10	802
	70 225/70R17 108T	RF RBL	6~7.5	748
	P235/70R17 108S	XL OWL/RBL	① 6~8	① 762
	LT245/70R17 119/116R	RBL	① 6.5~8	① 776
	P255/70R17 110S	OWL/RBL	① 6.5~8.5	① 790
	LT265/70R17 121/118R	RBL	① 7~8.5	① 804
	P265/70R17 113S	OWL/RBL	① 7~9	① 804
	LT285/70R17 121/118R	RBL	① 7.5~9	① 840
	LT315/70R17 121/118R	RBL	① 8.5~10	① 874
75	LT245/75R17 121/118R	RBL	① 6~7.5	① 807
80	LT235/80R17 120/117R	RBL	① 6~7.5	① 812
16 60	215/60R16 95H	RBL	6~7.5	664
	235/60R16 100H	RBL	6.5~8.5	688
	65 205/65R16 95H	RBL	5.5~7.5	672
	215/65R16 98H	RBL	6~7.5	686
	255/65R16 109H	RBL	7~9	738

Inch Series	Size	Side	Approved rim width	Overall Diameter
16 70	215/70R16 100S	RBL	5.5~7	708
	225/70R16 102H	RBL	① 6~7.5	① 722
	P235/70R16 107S	XL OWL/RBL	① 6~8	① 736
	235/70R16 106H	RBL	6~8	736
	P245/70R16 106S	OWL/RBL	① 6.5~8	① 750
	245/70R16 107H	RBL	6.5~8	750
	P255/70R16 109S	OWL/RBL	① 6.5~8.5	① 764
	P265/70R16 111S	OWL/RBL	① 7~9	① 778
	265/70R16 112T	RBL	7~9	778
	275/70R16 114H	RBL	7~9	792
	75 LT225/75R16 110/107R	OWL/RBL	① 6~7	① 750
	LT245/75R16 120/116R	OWL/RBL	① 6.5~8	① 774
	LT265/75R16 119/116R	OWL/RBL	① 7~8	① 804
	LT285/75R16 116/113S	RBL	① 7.5~9	① 834
	LT315/75R16 113S	RBL	① 8~10	① 878
80	175/80R16 91S	RBL	① 4.5~6	① 686
	205/80R16 104T	RF RBL	5~7	734
	215/80R16 103S	RBL	5.5~7	750
85	LT215/85R16 110/107R	OWL/RBL	① 5.5~7	① 772
	LT235/85R16 120/116R	OWL/RBL	① 6~7.5	① 806
15 70	205/70R15 96S	RBL	5~7	669
	215/70R15 98S	RBL	5.5~7	683
	P225/70R15 100S	OWL/RBL	① 6~7.5	① 697
	P235/70R15 102S	OWL/RBL	① 6~8	① 711
	255/70R15C 112/110S	RBL	7~8	739
	265/70R15 112T	RBL	7~9	753
75	LT215/75R15 100/97S	OWL/RBL	① 5.5~7	① 703
	LT235/75R15 104/101S	OWL/RBL	① 6~7	① 733
	P235/75R15 108S	XL OWL/RBL	① 6~8	① 733
80	175/80R15 90S	RBL	① 4.5~6	① 661
	195/80R15 96S	RBL	5~6.5	693
	215/80R15 102S	OWL/RBL	5.5~7	725
	225/80R15 105S	RBL	① 6~7.5	① 741
	30X9.50R15 104S	OWL/RBL	① 6.5~8.5	① 750
	31X10.50R15 109S	OWL/RBL	① 7~9	① 775
	32X11.50R15 113S	OWL/RBL	① 8~10	① 801
	33X12.50R15 108S	OWL/RBL	① 8.5~11	① 826

RF=Reinforced

XL=Extra Load

①=Approved rim width and overall diameter TRA yearbook 2008.

①=Approved rim width and overall diameter JATMA yearbook 2008.

RBL=Raised Black Letter

OWL/RBL = Outlined White Letter/Raised Black Letter