

Inch Series	Size	Side	Approved rim width	Overall Diameter
18 55	225/55R18 97V	RBL	Ⓟ 6~8	Ⓟ 705
	235/55R18 104V	RF RBL	6.5~8.5	715
60	225/60R18 100H	RBL	Ⓟ 6~8	Ⓟ 727
	235/60R18 103V	RBL	6.5~8.5	739
	255/60R18 112V	RF RBL	7~9	763
65	225/65R18 103H	RBL	6~8	749
17 55	225/55R17 97H	RBL	6~8	680
	235/55R17 99H	RBL	6.5~8.5	690
60	215/60R17 96H	RBL	6~7.5	690
	225/60R17 99H	RBL	6~8	702
65	P235/60R17 103H	XL RBL	Ⓟ 6.5~8.5	Ⓟ 714
	225/65R17 102H	RBL	6~8	724
65	235/65R17 108H	RF RBL	6.5~8.5	738
	265/65R17 112H	RBL	7.5~9.5	776
	275/65R17 115H	RBL	7.5~9.5	790
70	225/70R17 108H	RF RBL	6~7.5	748
16 60	215/60R16 95H	RBL	6~7.5	664
	235/60R16 100H	RBL	6.5~8.5	688
65	215/65R16 98H	RBL	6~7.5	686
	255/65R16 109H	RBL	7~9	738
70	215/70R16 100H	RBL	5.5~7	708
	225/70R16 102H	RBL	Ⓟ 6~7.5	Ⓟ 722
65	235/70R16 106H	RBL	6~8	736
	245/70R16 107H	RBL	6.5~8	750
	255/70R16 111H	RBL	6.5~8.5	764
	265/70R16 112H	RBL	7~9	778
	275/70R16 114H	RBL	7~9	792
15 70	205/70R15 96H	RBL	5~7	669
	215/70R15 98H	RBL	5.5~7	683
	255/70R15 108H	RBL	6.5~8.5	739
	255/70R15C 112/110R	RBL	7~8	739
	265/70R15 112H	RBL	7~9	753
75	P235/75R15 105H	RBL	Ⓟ 6~8	Ⓟ 733
	30X9.50R15 104S	OWL/RBL	Ⓟ 6~7.5	Ⓟ 750
	31X10.50R15 109S	OWL/RBL	Ⓟ 7~9	Ⓟ 775

RF=Reinforced

XL=Extra Load

Ⓟ=Approved rim width and overall diameter TRA yearbook 2008.

Ⓟ=Approved rim width and overall diameter JATMA yearbook 2008.

RBL=Raised Black Letter

OWL/RBL = Outlined White Letter/Raised Black Letter