

Inch Series	Size		Approved rim width	Overall Diameter
26 40	315/40R26 120V	RF	10.5~12.5	912
24 35	295/35R24 110V	RF	10~11.5	816
	305/35R24 112V	RF	10~12	824
	315/35R24 114V	RF	10.5~12.5	830
40	285/40R24 112V	RF	9.5~11	838
23 30	295/30R23 104V	RF	10~11	762
	35 285/35R23 107V	RF	9.5~11	784
	40 285/40R23 111V	RF	9.5~11	812
	305/40R23 115V	RF	10~12	828
22 30	265/30R22 97V	RF	9~10	719
	285/30R22 101V	RF	9.5~10.5	731
	35 255/35R22 99V	RF	8.5~10	737
	265/35R22 102V	RF	9~10.5	745
	285/35R22 106V	RF	9.5~11	759
	40 265/40R22 106V	RF	9~10.5	771
	285/40R22 110V	RF	9.5~11	787
	305/40R22 114V	RF	10~12	803
	45 285/45R22 114V	RF	9~10.5	815
	305/45R22 118V	RF	9.5~11.5	833
20 40	255/40R20 101V	RF	8.5~10	712
	275/40R20 106V	RF	9~11	728
	45 245/45R20 99V		7.5~9	728
	255/45R20 105V	RF	8~9.5	738
	275/45R20 110V	RF	8.5~10.5	756
	295/45R20 114V	RF	9.5~11	774
	50 245/50R20 102V		①7~8.5	①754
	255/50R20 109V	RF	7~9	764
	265/50R20 111V	RF	7.5~9.5	774
	285/50R20 112V		8~10	794
	305/50R20 120V	RF	8.5~11	814
	55 235/55R20 102V		6.5~8.5	766
	275/55R20 117V	RF	7.5~9.5	810
19 55	235/55R19 101V		①6.5~8.5	①741
18 55	235/55R18 100V		6.5~8.5	715
	60 225/60R18 100H		①6~8	①727
	235/60R18 103V		6.5~8.5	739
	245/60R18 105H		7.5~8.5	751
	65 235/65R18 106H		6.5~8.5	763
17 65	225/65R17 102H		6~8	724

RF=Reinforced

①=Approved rim width and overall diameter JATMA yearbook 2008.